


SUMMARY

01


FEEDBACK ABOUT THE CURRENT OCX SCHEMA (2.8.6) 02

PROPOSAL FOR FUTURE EVOLUTION





STRUCTURE OF THE SOLUTION



Copyright BV M&O 2022 4

OCX TEST EXCHANGES





















BULB PROFILE DEFINITION

Common definition: HP 180 X 10



In 2.8.6 format, *FlangeWidth* is mandatory




Different interpretation: some CAD solutions export the OCX model with *FlangeWidth* equal to 0 or generate an OCX file without this *FlangeWidth* attribute (not conform with the schema).

BV Position:

- To be conform with the schema 2.8.6 -> the *FlangeWidth* attribute is to be present.
- We will modify our import tool to manage FlangeWidth = 0.
- The schema should be corrected in the next version removing this FlangeWidth attribute.


ROOT POINT VS TRACE LINE DEFINITION



Simple solution for CADs: export the trace line (as the connection line between the stiffener and the plate) and to set a value to OffsetU.

The cross-section origin or root point is defined by the lower left corner of the enclosing bounding box.


- for T bar, the root point doesn't correspond to the attached point between the stiffener and the attached plating
- for I-beam / rectangular tube / pipe, the root point doesn't correspond to the center of gravity of the pillars



Actions:


- CAD solutions check if this convention is correctly applied / if not -> modify the export to follow it.
- Discussion if this root point definition should be reviewed to follow the normal CAD definitions.

INCLINATION / OPTIONAL FOR PILLAR



Due to the root point definition, it seems that an inclination definition is mandatory. In fact, a simple solution for CADs to adapt their trace line to this convention in the export is to set a value to OffsetU and OffsetV using the pipe parameters (Height or Diameter).

The local axis are deducted from the Inclination defined in the stiffeners/pillars.




Actions:

- CAD solutions export systematically this *Inclination* attribute.
- Revision of the format to define this *Inclination* attribute as mandatory.



ADD NEW ATTRIBUTES

As rule requirements, the renewal thickness / voluntary addition thickness when applicable are to be provided directly in the 2D drawings:



LONGITUDINALS


EXCEPT NOTED

EXCELL HOLED													
LOCATION	LONG. ID	SCANTLING											
UPPER DECK	28,29	FB1000X70AH40<68.5>											
2ND DECK		L 200X90X1(<7.5>, 14AH<11.5>											
3RD DECK		<u> </u>											

Actions:

Add these new attributes directly in the OCX format:

- renewal thickness
- voluntary addition thickness



WELDING INFORMATION

Current situation:

- Use of the welding booklet to review:
 - Welding consumables and procedure
 - Standard connections

		Required Throat Thickness, tw (mm), for a given Plate Thickness, t (web thickness in mm of the thiner plate in the connection)																															
	Note	5	5.5	6	6.5	7	7.5	8	8.5	9	9.5	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	Weld type
Stiffeners																																	
Stiffeners in general		. 3	. 3	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	4	4	4	4.5	4.5	. 5	. 5	5.5	5.5	5.5	5.5	5.5	6	Double continous
1	50% of span	3	3	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	4	4	Double continous
	At ends (where no end brackets are fitted)	3	3	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	4	4	4.5	5	5.5	5.5	6	6.5	6.5	7	7.5	7.5	8	8.5	9	9	9.5	10	10	10.5	Double continous

• Additional information directly on the 2D drawings for specific cases (ponctual load / pillar – equipment connections ...)

Proposal based on the 3D model

- Use of the welding booklet to review:
 - Welding consumables and procedure
 - Standard connections
- For specific cases, additional information directly on the 3D Model thanks to a new object type WELD (weld type / leg length ...)

Copyright BV M&O 2022 11





